PRODUCT DATA SHEET



ADVANCING HEALTHCARE TECHNOLOGY



PRODUCT CATEGORY:

PENDANT SERVICE SYSTEMS

PRODUCT NAME:

HU6-T22

PRODUCT DESCRIPTION:

CEILING MOUNTED PENDANT SERVICE SYSTEM



Product Codes: HU6-S2-01, HU6-S2-02, HU6-T12, HU6-T22

Area of Use: ICU, Resuscitation, Recovery Area, High Care, Trauma and Emergency.

Intended Use:

The pendant service system is ceiling mounted and is intended to supply one or more of the following medical services via movable service pillars which are attached to double articulated arms:

- electrical power up to 240 volts
- medical gases such as oxygen, nitrous oxide, carbon dioxide
- low pressure medical air for patient ventilation
- high pressure medical air for driving other medical devices
- vacuum and / or anaesthetic gas scavenging services

The unit can be fitted with equipment trays and equipment poles for medical equipment, monitors, life support systems, medical attachments etc. The movable unit is designed to enable the user to move the services to the optimum position for the procedure or treatment being performed on the patient.

The equipment is intended to be used by surgeons, anaesthetists, qualified Trauma, Theatre and Intensive / High Care nursing staff.



PRODUCT DATA SHEET

ADVANCING HEALTHCARE TECHNOLOGY



HU6-T22 SPECIFICATIONS

| SPECIFICATIONS: | |
|----------------------------|---|
| Construction: | The pillar and arm are manufactured from aluminium extrusion. |
| Surface Finish: | As a standard , fascia plates and horizontal arms offered in hard wearing powder coated RAL 9002 finish or vinyl wrapping. |
| Installation Position: | Vertical mounted, ceiling suspended. |
| Service Entry: | Ceiling void or via a core hole with services from the plant room. |
| High Voltage: | Standard: Socket with double pole miniature circuit breaker, overload protection, or to suit the specific requirements. |
| Low Voltage: | To suit specific requirements. E.g. Data, Telephone, Network plugs. |
| Medical Gas: | Various options are available. Medical Gas outlets are factory fitted and pressure tested. |
| Illumination: | Not applicable to this unit. |
| Customised Option: | Unit length and service requirement are manufactured to meet specific needs. |
| Product Payload: | 250 Kg per side |
| Product Weight: | 375 Kg |
| Total Suspended Weight: | 875 Kg |
| Rotation: | 320° |
| Centre to Centre Distance: | 800/600 mm |
| Suitable Accessories: | Medical Rail, Drip-hanger, Monitor Support System, Plastic Equipment Tray, Ambu-bag Holder, Extension Poles, Drawer Unit with Table Top and Equipment Clamps. |
| Certification: | CE |

•

TECHNICAL DRAWINGS







